





Advanced Automatic Inline Tray Sealer

The **MPE** i-4 Inline heat-sealing machine. Is built on **MPE** many years of extensive experience in the heat-sealing industry. The i-4 represents the culmination of this experience.

Standard Features

- E-RAM Sealing Technology
- On-line Systems and technical support via modem link, also allows direct software upgrades.
- RFID swipe card security access. With different level access for operators and engineers.
- Recipe driven automatic machine set-up.
- o Process control monitoring.
- All Electric Machine (no pneumatics)
- o Category 4 Safety System
- Up to 18 Cycles per min none-Gas
- Gas Flushing as standard (Modified Atmosphere)
- 1-5 Impression Tooling
- Easy and quick Tool Change
- o High force Electric seal
- o Fully automatic machine
- Robust machine simple, reliable, efficient
- Small footprint design saves valuable floor space
- Rapid changeover between tray sizes
- Self-centering tray guides.
- Maintenance friendly
- Advanced AI temperature control system for thin packaging.
- Film Snap detection.
- Active film torque system.
- Food industry approved construction
- Intuitive HMI system design.
- Can be operated from both sides.
- Tray crush avoidance system.
- Quick release conveyor system. For ease of cleaning and maintenance.
- Continues motion tray transfer system.
- Ancillary equipment Integration (Coders / Printers/ Depositors etc)
- MADE IN UK

🕾 Tel: 01663 732700 🛘 🖂 Email: sales@mpe-uk.com 🗸 Web: www.mpe-uk.com

Optional Features

- o Registered Film
- o Printer
- o High Oxygen
- o Inboard / Close cut film
- o Active conveyor
- o Vac/Gas flushing

Sealing capacity

| No of trays | Length | Width | Depth | Diameter |
|-------------|--------|-------|-------|----------|
| One | 300mm | 963mm | 200mm | 300mm |
| Two | 300mm | 481mm | 200mm | 300mm |
| Three | 300mm | 312mm | 200mm | 300mm |
| Four | 300mm | 228mm | 200mm | 228mm |
| Five | 300mm | 177mm | 200mm | 177mm |

Production capacity

| | Cycles per Minute | |
|--------------------|-------------------|--|
| Vacuum / Gas Flush | 12 | |
| Gas Flush | 14 | |
| Standard Seal | 18 | |

Packaging materials

| Trays |
|------------------|
| C·PET |
| A·PET |
| R∙PET |
| Polypropylene |
| PVC |
| Styrene |
| Board |
| Paper |
| Smooth Wall Foil |

Dimensions

| Height | 2080 mm | |
|--------|---------|--|
| Width | 850 mm | |
| Length | 3100 mm | |

Gas flush consumption

| Pressure | Flow | Pressure | Flow |
|----------|---------|----------|--------|
| 6 Bar | 50L/Min | 87psi | 1.7CFM |

Electrical supply

Electrical supply 400V 3 phase + neutral (fused at 16A)

Tel: 01663 732700

Email: sales@mpe-uk.com

■ Web: www.mpe-uk.com